

Electro Clean CF

Odourless, non-emulsifying degreaser.

- Special degreaser to remove oil- and grease contamination from machine- and motor components, transmissions, ball-bearings, cog-wheels, metal parts, etc.
- Appropriate to be used in garages, maintenance companies and workrooms
- Contains no chlorinated hydrocarbons
- Does not form an emulsion with water, the contaminated oil can be separated with an oil/water separator and then be recycled or destroyed; so waste-water problems are avoided
- It fulfils TL 6850-017, edition of the German Army, in which the amount of remaining oil after 5 minutes, following fixed standards, will be measured
- Odourless and powerful

Application

ELECTRO CLEAN CF can be used in combination with a brush or by spraying. To clean severely contaminated parts, it can be used in an immersion bath.

Directions for use

Immersion bath method

ELECTRO CLEAN CF is used undiluted and unheated in immersion bathes. Put the objects to be cleaned in the immersion bath and let them soak for a few hours. Then get them out of the bath and spray off with a powerful water beam.

ATTENTION: parts which should be absolutely free of rust/corrosion, should not be rinsed with water but with fresh ELECTRO CLEAN CF. Dry the parts afterwards with compressed air.

General cleaning

To clean contaminated parts and surfaces, ELECTRO CLEAN CF is to be used undiluted. Moisture the objects to be cleaned properly with the product. Depending on the character and amount of contamination let the product soak for 5 to 60 minutes. Meanwhile brushing will help. Afterwards the objects should be rinsed abundantly with water.

ATTENTION: parts which should be absolutely free of rust/corrosion, should not be rinsed with water but with fresh ELECTRO CLEAN CF. Dry the parts afterwards with compressed air.

NOTICE: cold degreasers may only be used in combination with oil/water separators. In order to guarantee an optimal separation of oil and water, cold degreasers should never be collected in oil/water separators together with emulsifying cleaning agents.

Properties

Clear, colourless, neutral and liquid degreasing agent based on among other things high-boiling aliphatic hydrocarbons. ELECTRO CLEAN CF does not evaporate too quick and always without a residue. ELECTRO CLEAN CF can be used on most metals, synthetics, rubber and hardened coatings.

Specific Gravity (20 °C)	: 0.78
Flash point (PMCC)	: > 61 °C
pH (1% solution)	: neutral

Nature of special risks and safety advice

See the Material Safety Data Sheet for details.

V-COM CHEMICALS Your chemical and industrial cleaning expert

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results. Contact details: sales@v-comchemicals.nl / +31 (0) 10 593 0203